

MEDICAL SUPERINTENDENT OFFICE GURU GOBIND SINGH HOSPITAL, FARIDKOT



Sadiq Road, Faridkot-151203 (Pb.) Indian
Ph. No. 01639-250098
Email- purchase.msoffice@gmail.com

No. Pur/2021/ 20045

Date:-13/12/2024

IT Cell
BFUHS, Faridkot (for uploading on uni website)

Sub:- Quotations for Purchase of Overhead Projector

Sealed quotations are invited for purchase of following item on the terms & conditions mentioned below:-

Sr. No.	Name of the item	Quantity Required
1	Overhead Projector (As per enclosed specifications)	01 No.

Terms & Conditions:-

Payment : By Cheque/RTGS

1. On receipt of material in good condition.
2. On receipt of material satisfactory report from the Concerned Deptt./Store.

F.O.R : Store Section, GGSMH, Faridkot.

Rate :
1. Taxes (as applicable), if any, be mentioned separately in the quotation.
2. The rates of taxes, be charged as per prevailing Govt. Notified Schedule.

Quantity/Item : Quantity may increase or decrease.

Others :
1. The firm should have PAN No, GST No and Bank Account No.
2. The material should be as per enclosed specifications.
3. The final decision of branded item would be reserves to consumer/concerned deptt.
4. Guarranty/Warranty must be quoted in the quotation.

You are therefore requested to quote your lowest rates of above items and submit Quotations addressed to **"The Medical Superintendent, Guru Gobind Singh Medical Hospital, Faridkot (Punjab)"**. The words **"Quotations for Purchase of Overhead Projector"** may please be inscribed on top of the envelope.

The Medical Superintendent reserves the right to reject the quotations without assigning any reason.

The sealed quotations should reach this office on or before 27/12/21 by 5.00 PM through **Registered/Speed Post/Traceable Courier** only.


Medical Superintendent

1. Notice Board.

Projection Technology		RGB liquid crystal shutter projection system
Specifications of Main Parts		
LCD	Size	0.61" (1.549 cm)
Projection Lens	Native Resolution	Full HD
	Type	Optical Zoom (Manual) / Focus (Manual)
	F-Number	1.58 - 1.70
	Focal Length	14.06 mm - 16.82 mm
	Zoom Ratio	1 - 1.2
Lamp	Throw Ratio	1.02 - 1.23 (Wide - Tele)
	Type	210W UHE
	Life (Normal / Eco)*	6,000 hours / 12,000 hours
Screen Size (Projected Distance)		
Zoom : Wide		30" to 300" (67 cm to 686 cm)
Zoom : Tele		30" to 300" (81 cm to 828 cm)
Standard Size		60" (152.4 cm) screen (135 cm x 164 cm)
Brightness*		
Colour Light Output (Normal / Eco)		3,400 lm / 2,200 lm
White Light Output (Normal / Eco)		3,400 lm / 2,200 lm
Contrast Ratio		16,000:1
Internal Speaker(s)		
Sound Output		2W Monaural
Geometric Correction		
Vertical / Horizontal Keystone		±30° / ±30°
Auto Keystone Correction		Yes (Vertical)
Horizontal / Side Keystone Correction		Yes
Quick Corner		Yes
Lens Shift Range		
Lens Shift		N/A
Connectivity		
Analog Input	D-Sub 15pin	1 (Blue)
	Composite	1 (Yellow)
Digital Input	HDMI	2 (one of terminal supports MHL)
Audio In		2 RCA (White x 1, Red x 1)
Audio Out		Stereo mini x 1
USB Interface	USB Type A	1 (for USB Memory, USB Document Camera, Firmware Update)
	USB Type B	1 (for USB Display Mouse, K/B, Control, Firmware Update)
Network		Built-in
Wireless Specifications		
(Built-in Wireless LAN Unit)		
Supported Speed For Each Mode		IEEE 802.11b (2.4GHz): 11 Mbps*, IEEE 802.11g (2.4GHz): 54 Mbps*, IEEE 802.11n (2.4GHz): 72.2 Mbps*, IEEE 802.11a (5GHz): 54 Mbps*, IEEE 802.11n (5GHz): 150.0 Mbps* Infrastructure, Access Point
Supported Connection Mode		Access Point: WPA2-PSK (AES), Infrastructure: WPA2/WPA3-PSK, WPA2/WPA3-EAP
Wireless LAN Security		
Wireless Specifications (Screen Mirroring)		
Supported Speed For Each Mode		IEEE 802.11g (2.4GHz): 54 Mbps, IEEE 802.11n (2.4GHz): 130.0 Mbps, IEEE 802.11a (5GHz): 54 Mbps, IEEE 802.11n (5GHz): 270.0 Mbps, IEEE 802.11ac (5GHz): 780Mbps WiFi Direct
Supported Connection Mode		WPA2-PSK (AES)
Supported Security Type		
Adjustment Functions		
Frame Interpolation		N/A
Detail Enhancement		Yes
Split Screen		Yes
Operating Temperature		5 - 40 °C <41 - 104 °F (0 m / 0 ft - 2,286 m / 7,500 ft)
Operating Altitude		5 - 35 °C <41 - 95 °F (over 2,286 m / 7,500 ft) with 20% - 80% humidity, No condensation
Direct Power On/Off		0 - 3,048 m <0 - 10,000 ft>
Start-Up Period		Yes about 6 seconds
Cool Down Period		Warm-up period: 30 seconds
Power Supply Voltage		Instant Off
Power Consumption (220 - 240V)		100 - 240 V AC ±10%, 50/60 Hz
Lamp On (Normal / Eco)		327W / 225W
Standby (Network On / Off)		2.0W / 0.3W