



Baba Farid University of Health Sciences, Faridkot

Sadiq Road Faridkot – 151203 (Pb) India

Phone: 01639-256232, 256236

Fax: 01639-256234

Web: www.bfuhs.ac.in

e-mail: upfdbfuhs@gmail.com

No.16-BFUHS/(UPFD-02)2021/ 5083

Date : 12-3-2021

Sub: Quotations for purchase of Passbook Printer.

Sealed quotations are invited for purchase of 02 nos. Passbook Printer as per attached specifications, on the following term and conditions:-

Terms and conditions:-

1. Payment : By Cheque on receipt of material in good condition and after satisfactory inspection report.
2. FOR : General Store, GGSMH, Faridkot
3. Rate : Inclusive of all taxes or taxes (as applicable), if any, be mentioned separately in the quotation.
4. Warranty/guaranty if any may be mentioned.
5. Validity : Rates should be valid for one year.

Quotation must be submitted through post/trackable courier. By hand quotations will not be entertained.

It is further mentioned that only the terms & conditions mentioned by the University on quotation performa will be considered for supply order. Moreover, the rates be quoted as per specifications mentioned in this quotation letter.

You are requested to send your quotation in a sealed cover, addressed to **the Registrar, Baba Farid University of Health Sciences, Sadiq Road, Faridkot (Punjab)** and the words "QUOTATION FOR PASSBOOK PRINTER" may please be inscribed on top of the envelope.

Last date for receipt of quotation in the university office is **25.03.2021 by 5.00 PM**


Prof. In-charge (UPFD)

Printing Technology:

Print Method: Impact dot matrix **Print Direction:** Bi-direction with logic seeking **Colour:** Black **Number of Pins in Head:** 24 pins **Control Code:** PR2 emulation, ESC/P2, IBM PPDS emulation, IBM 4722 emulation*

Print Speed:

High Speed Draft:(PR2 emulation) 10cpi: 480 cps

(PR2 emulation) 12cpi: 432 cps

(ESC/P2) 10cpi: 480 cps

(ESC/P2) 12cpi: 576 cps **Draft:**(PR2 emulation) 10cpi: 360 cps

(PR2 emulation) 12cpi: 360 cps

(ESC/P2) 10cpi: 360 cps

(ESC/P2) 12cpi: 432 cps **NLQ:**(PR2 emulation) 10cpi: 180 cps

(PR2 emulation) 12cpi: 180 cps **Letter Quality:**PR2 emulation) 10cpi: 120 cps

(PR2 emulation) 12cpi: 144 cps

(ESC/P2) 10cpi: 120 cps

(ESC/P2) 12cpi: 144 cps

Reliability:

MVBF:7 million lines **MTBF:**10,000 **Power On Hours (POH)** **Printhead Life:**400 million strokes/wire

Print Characteristics:

Character Sets:International, PC-437 International, OCR-A
Barcode:PR2: EAN-13, EAN-8, Interleaved 2 of 5, UPC-A, Code 39, Coda bar (NW7), Industrial 2 of 5
ESC/P: EAN-13, EAN-8, Interleaved 2 of 5, UPC-A, UPC-E, Code 39, Code 128, POSTNET

Paper Path:

Manual Insertion:Front in, Front out / Front in, Rear out

Paper Media:

Cut Sheet (Single Sheet):Width: 65 x 67 mm

Length: 245 x 297 mm

Thickness: 0.065 - 0.19 mm

Weight: 52 - 157 g/m²
Cut Sheet (Multi-part Forms):Width: 65 x 67 mm

Length: 245 x 297 mm

Copies: 1 original + 6 copies

Thickness: 0.12 - 0.53 mm

Weight (per sheet): 34 - 50 g/m²
Line Spacing:4.23 mm (1/6 inch)

Passbook:

Width:110 - 241.3mm
Length:Horizontal seam: 127 - 220mm

Vertical seam: 85 - 220mm
Total Thickness:Max. 2.6mm (open passbook)
Weight:95 - 116 g/m²

Supported OS and Applications:

Supported OS: Windows 7 / 8 / 8.1 / 10

Consumables:

Ribbon Cartridge Black: 5 million characters (LQ 10cpi, 48 dots/character)

10 million characters (LQ 10cpi, 24 dots/character)

Acoustic Noise: 53 dB(A) (w/o MSRW)

55 dB(A) (w/ MSRW)

Input Data Buffer:

Input Data Buffer: 64 KB

Interface:

Interface: Bi-directional Parallel

9-pin Serial

USB 2.0 Full speed