



Baba Farid University of Health Sciences, Faridkot

Sadiq Road Faridkot – 151203 (Pb) India

Phone: 01639-256232, 256236

Fax: 01639-256234

Web: www.bfuhs.ac.in

E-mail: generalinfo@bfuhs.ac.in

No.16 BFUHS (UPFD)2018/ 23 019

Dated: 4/10/18

web site

Subject: Quotations for purchase of UPS.

Sealed quotations are invited for purchase of **10** nos. UPS as per attached specifications and following terms and conditions:-

Terms and conditions: -

1. Payment : By Cheque on receipt of material in good condition and after satisfactory inspection report.
2. Delivery : General Store, GGSMH, Faridkot
3. Rate : Inclusive of all taxes or taxes (as applicable), if any, be mentioned separately in the quotation.
4. Validity : Rates should be valid for one year.
5. Warranty/guaranty if any may be mentioned.

6.Quotation must be submitted through post/trackable courier. By hand quotations will not be entertained.

It is further mentioned that only the terms & conditions mentioned by the University on quotation performa will be considered for supply order.

You are requested to send your lowest quotation in a sealed cover, addressed to the Registrar, Baba Farid University of Health Sciences, Sadiq Road, Faridkot (Punjab) and the words "QUOTATION FOR UPS" may please be inscribed on top of the envelope.

Last date for receipt of quotation in the university office is **18.10.2018** by 5.00 PM

Prof. In-charge (UPFD)

Introducing next gen 600VA UPS

For Single PC use

BX600C-IN

- 1 Three battery backed outlets with continuous surge protection
- 2 Faster charging 4-6 hours
- 3 **Battery Saver** : Increases battery life upto two times. Experience consistent runtime through the battery life[#]
- 4 Wide input voltage window : 145 V to 290 V
- 5 Compatible with low power loads e.g. wifi router, DSL modem
- 6 2 Year Warranty: covers parts & labor, including battery
- 7 Cold start capability allows the load to power on just on battery
- 8 Automatic Voltage Regulation (AVR) corrects incoming voltage
- 9 Beeper Delay : Stays quiet during changeover from mains to generator
- 10 Separate Charging LED

Product feature	BX600C-IN
Input	
Voltage	230 VAC nominal
Frequency	45 – 65 Hz
Brownout Transfer	145 VAC typical
Over-voltage Transfer	290 VAC typical
Output	
UPS Capacity (total)	600VA/360W
Voltage on Battery	230 VAC typical (stepped approximated sine wave)
Frequency – On Battery	50Hz typical
Transfer Time	4-8 ms typical
Protection and Filtering	
AC Surge Protection	Full time, 255 joules
Battery	
Type (maintenance-free)	12V, 7.2 Ah
Typical recharge time	4-6 hours
Physical	
Net Weight	4.7 Kg
Dimensions (H x W x D)	21.8 cm x 10.7 cm x 23.7 cm
Operating Temperature	0° C to 40° C
Storage Temperature	-15° C to 45° C
Operating Relative Humidity	0 to 95% non-condensing
3 power outlets	With battery backup and surge protection
Power Cord	1.2 meters